The perfect transmitter made from expert know-how

A typical pressure transmitter has three general functional

- The electronics
- The sensing element
- The packaging

combination that determines the performance of the products. All Danfoss pressure transmitters are certified according to ISO/TS 16949:2009 and ISO 14001:2004.

1 Electronics

Danfoss pressure transmitters are available with analogue or digital electronic solutions and offer unique specifications in terms of:

- Accuracy
- Temperature range coverage
- EMI/RFI protection
- Multi-variable transmitter function
- Pressure
- Pressure and switch function

2 Sensing element

Offering two sensing technologies Danfoss is able to cover the versatile application requirements with highly competitive solutions. Both technologies are designed to operate in severe environments:

- Piezoresistive semi-conductor technology covering pressure ranges from 1 to 600 bar. This technology is available in absolute or gauge versions
- Thin-film technology is mainly used for high-pressure applications up to 2200 bar. This technology is available in gauge version

3 Packaging The transmitter design offers

long-life stability through:

- High shock and vibration stability
- High enclosure grade (special version up to IP69K)
- Pulse restriction solution which prevents liquid hammering and cavitation A
- Wetted parts that are all made from stainless steel

Engineering Tomorrow



Danfoss is a leading global player within the development and production of mechanical and electronic products and controls. Since 1933, our extensive know-how has made modern life easier and we continue to break new ground within our core business areas.

Every day, more than 250,000 items are produced at 70 factories in 25 countries. Impressive as these figures are, we are most proud of the way our dedicated employees apply the high-quality components in customer solutions, adding value to the end products. Building strong partnerships is of great importance to us, because it is purely by understanding our customers' needs that we can meet the expectations of tomorrow.

Learn more at ia.danfoss.co.uk

Danfoss Limited - Industrial Automation

Capswood · Oxford Road, Denham · Bucks · UB9 4LH · United Kingdom · ia@danfoss.com Tel.: 0870 241 7030 · Fax: 0870 241 7035

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved

IC.PB.P00.F1.12 | 520B7059



This is also true in Industrial Automation, a Danfoss entity dedicated to focusing on the industrial world of today. Through us, you gain access to the entire Danfoss pool of technologies, with special emphasis on sensors and controls.

We offer safer, more reliable and more efficient solutions in a close cooperation based on firm values.



Pressure Transmitters designed for customer needs

A pressure transmitter overview



© Danfoss | DCS (im) | 2015.12

We've made your challenges our business

Machine and

Engines

Industrial hydraulics

When you choose Danfoss as your supplier of pressure transmitters, you choose a dedicated partner who truly understands the challenges in your specific applications. Years of experience allow us to provide you with advanced solutions that will meet your every requirement in terms of

£68€

both performance and life cycle cost. Choose from our wide range of standard devices or team up with our worldwide transmitter experts to design a customised solution for your

Heating and

sanitation

Marine and railway equipment

Marine, Mobile Hydraulics and Railways

The increasing global focus on environmental and safety legislation calls for more control and automation. Danfoss accommodate this by optimising product functions and specifications, allowing you to comply with the new demands. Our wide transmitter range comprises solutions for:

- Marine equipment
- Mobile hydraulic equipment
- Railway equipment

▋ᢒ᠊ᡲᡗᢛ᠋ equipment

Industrial Hydraulics, AirCompressors, Water Pumps and Industrial Engines

Within machines and equipment the transmitter specifications depend on the specific application. Close cooperation with customers has allowed us to develop dedicated transmitter solutions for:

Sterilisers, Autoclaves, Boiler and Boiler Room Equipment

Energy efficiency and safety are frequent challenges in heating and sanitation applications. The answer is highly reliable and accurate measurement, which is achieved by unique process control. For this • Water pumps and air compressors specific purpose, Danfoss has developed a unique solution.

0: 🕛



Wind Turbines and Electric Power

One of the most distinct global challenges now and in the future is how to produce energy in a both efficient and environmentally friendly way. In cooperation with some of the leading manufacturers, Danfoss has developed – and is continuously refining – solutions for:

- Wind turbines
- Gen sets



STANDARD MBS 1700 WITH PULSE-SNUBBER MBS 1750 Transportation of 🍐 Heating and sanitation **9** Machine and equipment **B**⁰ Energy Piezo Sensor technology resistive Accuracy FS (max) ±1% Max. measuring range [bar] $0 - 400^{1}$ $0 - 5800^{1}$ Max. measuring range [psi] 4 – 20 mA Output signal _ _ °C -40 − 85 °C Medium -40 – 185 °F temperature _ IP65 **Enclosure IP** Wetted parts material AISI 316L AISI 316L, Housing material PA 6.6 Zero point and span adjustment Marine approvals **ATEX** approval **UL Hazloc**

Pressure ranges 0 – 6 bar – 0 – 25 bar in relative (gauge) Pressure ranges 0 – 87 psi — 0 – 363 psi in relative (gauge)



		PRESSURE TRANSMITTERS OVERVIE	w		
MBS 3000	MBS 3200	MBS 3100	MBS 5100	ЕМР	MBS 4510
MBS 3050	MBS 3250	MBS 3150	MBS 5150		
ŧ	ŧ	£	£	£	
l by to	.				
*	<u>s</u>		<u> </u>		*
Piezo resistive	Piezo resistive	Piezo resistive	Piezo resistive	Piezo resistive	Piezo resistive
± 1%	± 1%	± 1%	± 0.3%	± 0.5%	± 0.5%
0 – 600	0 - 600	0 - 600	0 - 600	0 - 400	0 – 25
0 – 9000	0 – 9000	0 – 9000	0 – 9000	0 – 6000	0 – 360
4 – 20 mA	4 – 20 mA	4 – 20 mA	4 – 20 mA	4 – 20 mA	4 – 20 mA
Absolute voltage	Absolute voltage	-	-	-	-
-	-	-	-	-	-
-40 – 85 °C	-40 – 125 ℃	-40 − 85 °C	-40 − 85 °C	-40 − 100 °C	-40 − 85 °C
-40 – 185 °F	-40 – 257 °F	-40 – 185 °F	-40 – 185 °F	-40 – 212 °F	-40 – 185 °F
0					
IP65 IP67	IP65 IP67	IP65 IP67	IP65	IP67	IP65
AISI 316L	AISI 316L	AISI 316L	AISI 316L	AISI 316L	AISI 316L
AISI 316L, PA 6.6	AISI 316L, PA 6.6	AISI 316L, PA 6.6	AISI 316L, PA 6.6	AI	AISI 316L, PA 6.6
			•	•	•
		•	•	•	
Zone 2	Zone 2	Zone 2	Zone 2	Zone 2	Zone 2
Class 1, Div. 2	Class 1, Div. 2	Class 1, Div. 2	Class 1, Div. 2	All transmitters are available with a variety of electrical and	Class 1, Div. 2